

STAINLESS STEEL SNAP HOOK

Accessories | 316 Stainless Steel



01 TECHNICAL SPECIFICATIONS

PART NO.	WEBBING	A mm	B mm	C mm	D mm	E mm	F mm	WT g
0240	25mm	16	32	4	66	36	12	50
0241	25mm	16	35	4	72	36	12	46
0242	25mm	16	31	4	71	36	11	46

A = Internal Width · B = Internal Height · C = Thickness
 D = External Height · E = External Width · F = Length

02 OVERVIEW

Makefast Stainless Steel Snap Hook — part of the Accessories range. Engineered for defence and tactical programmes with verified mechanical performance. Available in 3 webbing variants: 0240 (25mm), 0241 (25mm), 0242 (25mm).

03 CUSTOMISATION

■ CUSTOM DIMENSIONS & TOLERANCES	■ 316 STAINLESS STEEL FINISH	■ POWDER COAT OR ANODISED OPTIONS
■ RAL COLOUR MATCHING	■ OEM VOLUME B2B SUPPLY	■ UK MANUFACTURED & CERTIFIED

04 COMPLIANCE & STANDARDS

ISO 9001:2015	NCAGE	JOSCAR	MIL-A-8625
CERT. FM60306	NATO CODE U2DU3	STATUS Registered	FINISH Available

Breaking loads apply to 316 Stainless Steel variants only. Values are guidance for straight-pull testing and do not form part of any warranty. SWL recommended at 1/5 of BL. All dimensions are nominal.