

PART REF. 0103 – 0310 (2 variants)

# HARNES BUCKLE

Interlocking Buckles | 316 Stainless Steel



## 01 TECHNICAL SPECIFICATIONS

| PART NO. | WEBBING | A mm | B mm | C mm | D mm | E mm | BL kg | WT g |
|----------|---------|------|------|------|------|------|-------|------|
| 0103     | 45mm    | 3    | 46.7 | 1.5  | 62   | 71   | 350   | 44   |
| 0310     | 50mm    | 5.2  | 50.4 | 3    | 70.5 | 98   | 800   | 120  |

A = Internal Width · B = Internal Height · C = Thickness  
D = External Height · E = External Width

## 02 OVERVIEW

Makefast Harness Buckle — part of the Interlocking Buckles range. Engineered for defence and tactical programmes with verified mechanical performance. Available in 2 webbing variants: 0103 (45mm), 0310 (50mm).

## 03 CUSTOMISATION

|                                  |                              |                                   |
|----------------------------------|------------------------------|-----------------------------------|
| ■ CUSTOM DIMENSIONS & TOLERANCES | ■ 316 STAINLESS STEEL FINISH | ■ POWDER COAT OR ANODISED OPTIONS |
| ■ RAL COLOUR MATCHING            | ■ OEM VOLUME B2B SUPPLY      | ■ UK MANUFACTURED & CERTIFIED     |

## 04 COMPLIANCE & STANDARDS

|                      |                        |                          |                         |
|----------------------|------------------------|--------------------------|-------------------------|
| <b>ISO 9001:2015</b> | <b>NCAGE</b>           | <b>JOSCAR</b>            | <b>MIL-A-8625</b>       |
| CERT. <b>FM60306</b> | NATO CODE <b>U2DU3</b> | STATUS <b>Registered</b> | FINISH <b>Available</b> |

Breaking loads apply to 316 Stainless Steel variants only. Values are guidance for straight-pull testing and do not form part of any warranty. SWL recommended at 1/5 of BL. All dimensions are nominal.