

NYLON HIGH LOAD RING

Lightweight Plastics | 316 Stainless Steel



FIG. 01 NYLON HIGH LOAD RING

RENDER | NTS

01 TECHNICAL SPECIFICATIONS

PART NO.	WEBBING	A mm	B mm	C mm	D mm	E mm	BL kg	WT g
3294	40mm	40	40	10	60	60	180	122

A = Internal Width · B = Internal Height · C = Thickness
D = External Height · E = External Width

02 OVERVIEW

Makefast Nylon High Load Ring — part of the Lightweight Plastics range. Engineered for defence and tactical programmes with verified mechanical performance. Available in 1 webbing variant: 3294 (40mm).

03 CUSTOMISATION

<ul style="list-style-type: none">CUSTOM DIMENSIONS & TOLERANCES	<ul style="list-style-type: none">316 STAINLESS STEEL FINISH	<ul style="list-style-type: none">POWDER COAT OR ANODISED OPTIONS
<ul style="list-style-type: none">RAL COLOUR MATCHING	<ul style="list-style-type: none">OEM VOLUME B2B SUPPLY	<ul style="list-style-type: none">UK MANUFACTURED & CERTIFIED

04 COMPLIANCE & STANDARDS

ISO 9001:2015	NCAGE	JOSCAR	MIL-A-8625
CERT. FM60306	NATO CODE U2DU3	STATUS Registered	FINISH Available

Breaking loads apply to 316 Stainless Steel variants only. Values are guidance for straight-pull testing and do not form part of any warranty. SWL recommended at 1/5 of BL. All dimensions are nominal.