

# O RING

Rings, Dees & Triangles | 316 Stainless Steel



FIG. 01 O RING

RENDER | NTS

## 01 TECHNICAL SPECIFICATIONS

PART NO.	WEBBING	A mm	B mm	C mm	BL kg	WT g
0635	25mm	25	25	4	2750	9
6151	40mm	40	40	5	1750	18
0120	50mm	50	50	6,4	2750	44

A = Internal Width · B = Internal Height · C = Thickness

## 02 OVERVIEW

Makefast O Ring — part of the Rings, Dees & Triangles range. Engineered for defence and tactical programmes with verified mechanical performance. Available in 3 webbing variants: 0635 (25mm), 6151 (40mm), 0120 (50mm).

## 03 CUSTOMISATION

■ CUSTOM DIMENSIONS & TOLERANCES	■ 316 STAINLESS STEEL FINISH	■ POWDER COAT OR ANODISED OPTIONS
■ RAL COLOUR MATCHING	■ OEM VOLUME B2B SUPPLY	■ UK MANUFACTURED & CERTIFIED

## 04 COMPLIANCE & STANDARDS

<b>ISO 9001:2015</b>	<b>NCAGE</b>	<b>JOSCAR</b>	<b>MIL-A-8625</b>
CERT. <b>FM60306</b>	NATO CODE <b>U2DU3</b>	STATUS <b>Registered</b>	FINISH <b>Available</b>

Breaking loads apply to 316 Stainless Steel variants only. Values are guidance for straight-pull testing and do not form part of any warranty. SWL recommended at 1/5 of BL. All dimensions are nominal.